

What is claimed is:

1. A resin sealing method for sealing a semiconductor chip flip-chip bonded with a substrate, the method comprising:

covering with a release film a face of an upper mold including a cavity recess portion and a resin pass communicating with the cavity recess portion;

putting the semiconductor chip with the substrate in the cavity recess portion;

clamping the semiconductor chip with the substrate by the upper mold and the lower mold;

delivering under pressure a sealing resin to a clearance between the semiconductor chip and the substrate with priority to perform under-fill molding and to form a molded component; and

separating a component gate runner connected to the under-fill portion, at the end of the substrate.

2. The resin sealing method as set forth in claim 1, further comprising:

protruding a movable block secured in the upper mold, into the cavity recess portion at both side faces of the semiconductor chip to push the release film to the semiconductor chip before performing the under-fill molding;

retreating the movable block; and

sealing both the side faces of the semiconductor chip with

resin.

3. The resin sealing method as set forth in claim 1, wherein resin is sealed so that the resin molding thickness of a portion that communicates from the substrate end of a molded component gate runner to the under-fill portion is made thinner at the pot side than that at the substrate end.

4. The resin sealing method as set forth in claim 1, wherein resin is sealed so that a V-shaped groove is formed at the substrate end position of a molded component gate runner remaining on the substrate.

5. The resin sealing method as set forth in claim 1, wherein a movable gate pin is provided at the substrate end position of the upper mold so as to protrude with respect a resin pass, and by closing the resin pass by the movable gate pin after the under-fill molding is completed, resin is sealed by pushing a sealing resin at the substrate end position back to the pot side.

6. The resin sealing method as set forth in claim 1, wherein a movable runner block is provided in the upper mold so as to protrude from the substrate end to the resin pass that communicates with the cavity recess portion, and by closing the resin pass by the movable runner block after the under-fill

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

7. A resin sealing apparatus for sealing a clearance between a semiconductor chip and a substrate flip-chip bonded to the semiconductor chip with resin, the apparatus comprising:

a lower mold on which a semiconductor chip with the substrate is placed,

an upper mold defining a cavity recess portion for accommodating the semiconductor chip with the substrate and a resin pass communicating with the cavity recess portion; and

a release film that covers the cavity recess portion and the resin pass;

wherein a sealing resin is delivered under pressure to the clearance between the semiconductor chip and substrate with priority to perform under-fill molding; and

the semiconductor chip is sealed with resin, with a molded component gate runner to be connected to the under-fill portion remaining on the substrate.

8. The resin sealing apparatus as set forth in claim 7, further comprising a movable block at both side faces of the semiconductor chip, the movable block provided in the upper mold to protrude into the cavity recess portion,

wherein the movable block is caused to protrude in advance into the cavity recess portion, under-fill molding is performed with the release film pushed to the substrate, and both side faces of the semiconductor chip are sealed with resin after

retreating the movable block.

9. The resin sealing apparatus as set forth in claim 7, wherein the cross section of a resin pass at a portion that communicates from the substrate end of the metallic mold gate runner formed on the upper mold to the cavity recess portion is formed to be smaller than the cross section of the resin pass at a portion that communicates from the substrate end to a pot.

10. The resin sealing apparatus as set forth in claim 7, wherein the semiconductor chip is chamfered at the upper edge portion including at least respective corners.

11. The resin sealing apparatus as set forth in claim 7, further comprising a movable gate pin provided at the substrate end position of the upper mold to protrude with respect to the resin pass,

wherein the semiconductor chip is sealed with resin by pushing the sealing resin at the substrate end position back to the pot side by closing the resin pass by the movable gate pin after the under-fill molding is completed.

12. The resin sealing apparatus as set forth in claim 7, further comprising a movable runner block provided in the upper mold to protrude from the substrate end to the resin pass that

[illegible]

- 29 -